



<i>werkbreedte</i> <i>largeur de travail</i> <i>working width</i> <i>Arbeitsbreite</i>		
A	B	C
1750	1880	2600
2000	2130	2850
2200	2330	3050
2500	2630	3350
3000	3130	3850
3300	3430	4150

D500 S		052.132.0006A
<i>Rolsnelheid</i> <i>Vitesse repassage</i>	1.5 – 5.5m/min *12m/min	<i>Mangelgeschwindigkeit</i> <i>Ironing speed</i>
<i>Rol aandrijfmotor</i> <i>Moteur entraînement</i>	0.37kw – 1500 rpm *1.5kw – 1500 rpm	<i>Walzenantriebmotor</i> <i>Roll drive motor</i>
<i>Rol afzuigmotor</i> <i>Moteur aspiration</i>	0.25kw – 3000 rpm	<i>Absaugmotor</i> <i>Exhaust motor</i>
<i>Motor hydr. pomp</i> <i>Moter pompe hydr.</i>	0.37kw – 1500 rpm	<i>Motor hydr. Pompe</i> <i>Moter hydr. pump</i>
<i>Stoomdruk</i> <i>Pression de la vapeur</i>	Min.: 6Bar Max.: 12Bar Aanbevolen: 10Bar Recommandé Empfohlen Recommended	<i>Dampfdruck</i> <i>Steam pressure</i>

①	<i>Elektrische aansluiting</i> <i>Connection électrique</i> <i>Strom Anschluss</i> <i>Electrical connection</i>	230V : 3 x 4mm ² + PE (16A) 400V : 3 x 4mm ² + N + PE (16A)
②	<i>Afzuiging dampen</i> <i>Sortie buëes</i> <i>Wrasenausgang</i> <i>Vapour outlet</i>	Ø75
③	<i>Stoominlaat</i> <i>Entrée vapeur</i> <i>Dampfanschluss</i> <i>Steam inlet</i>	5/4"
④	<i>Stoomuitlaat</i> <i>Sortie vapeur</i> <i>Dampfausgang</i> <i>Steam outlet</i>	3/4"